

Application No. 10/733,880

PATENT
Docket No. 58013-027100**AMENDMENTS TO THE CLAIMS****Claim 1 (Canceled)****Claim 2 (Currently amended):** A portable light for mounting on a support comprising:

an anchor to be secured with a support;

a housing portion mounted to the anchor, the housing portion including a head for
the a light source;a switch for the light source, the switch being operable by movement of the head
for the light source relative to the housing; anda base plate cooperating with the anchor, the light source being mounted relative
to the anchor on a position opposite to the base plate.**Claim 3 (Original):** A light as claimed in Claim 2, wherein the base plate and the anchor are
hingedly connected.**Claim 4 (Previously Presented):** A light as claimed in Claim 2 ~~4~~, wherein the base plate and
the anchor are hingedly connected, and a spring urging the base plate and the anchor towards
each other.**Claim 5 (Original):** A light as claimed in Claim 4, wherein the base and the anchor effectively
form a clip for securing the light to a support, such that the material for the support is locatable
between the base and the anchor, and thereby the light is secured to the support for the light.**Claim 6 (Previously Presented):** A light as claimed in Claim 2, wherein the head is hingedly
movable relative to the housing, and wherein the switch is operable to turn the light source on
when the head is moved from the housing.**Claim 7 (Previously Presented):** A light as Claimed in Claim 2, wherein the head includes at
least two light sources, the light sources being angled relative to the head to extend a field of
illumination forwardly from the rear of the head toward the forward end of the head, and wherein
the field of illumination partly overlaps in the area at the forward end of the housing.

Application No. 10/733,880

PATENT
Docket No. 58013-027100

Claim 8 (Original): A light as claimed in Claim 7, wherein the two light sources are spaced apart at a position remote from the forward end of the housing and the rear end of the housing.

Claim 9 (Previously Presented): A light as claimed in Claim 2, wherein the head is mounted on a top of the housing, the top being on the side remote from the anchor, and the head being for clipping engagement into an indent formed on a top face of the housing.

Claim 10 (Original): A light as claimed in Claim 9, wherein the head includes a protrusion, the protrusion being for extending through an aperture in a top face the housing, the protrusion acting to operate a switch when the protrusion moves between a position relative to the housing thereby to activate a switch between closure and opening.

Claim 11 (Original): A light as claimed in Claim 10, wherein the protrusion is relatively fixed on an under plate of the head, and the activation of the switch being effected by the location of the head relative to the position of the housing.

Claim 12 (Original): A light as claimed in Claim 11, wherein the housing and anchor are fixedly formed relative to each other.

Claim 13 (Original): A light as claimed in Claim 12, including a friction element in a hinge between the head and the housing, thereby to inhibit movement between the head and housing.

Claim 14 (Currently amended): A portable light for mounting on a support comprising:

an anchor to be secured with a support;

a housing portion mounted to the anchor, the housing portion including a head for ~~the~~ a light source;

a switch for the light source, the switch being operable by movement of the head for the light source relative to the housing;

a base for the light; and

the base and the anchor effectively forming a clip for securing the light to a support, such that the material for the support is locatable between the base and the anchor, and thereby the light is secured to the support for the light.

Application No. 10/733,880

PATENT
Docket No. 58013-027100

Claim 15 (Original): A light as claimed in Claim 14, wherein the head is hingedly movable relative to the housing, and wherein the switch is operable to turn the light source on when the head is moved from the housing.

Claim 16. (Canceled)

Claim 17 (Canceled)

Claim 18 (Canceled)

Claim 19 (Canceled)

Claim 20 (Canceled)

Claim 21 (Currently amended): A portable light for mounting on a support comprising:

an anchor to be secured with a support;

a housing portion mounted to the anchor, the housing portion including a head for the a light source;

a switch for the light source, the switch being operable by movement of the head for the light source relative to the housing; and

a base cooperating with the anchor, the light source being mounted relative to the anchor on a position opposite to the base.